

Smirkové lamelové kotouče s upínacím otvorem

Typ: BK

Korund: P- 40, 60, 80, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 40, 60, 80, 120					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BK 100 x 30 - 20	4 800	6 800	BK 130 x 25 - 15	4 800	6 800
BK 100 x 30 - 26	4 800	6 800	BK 130 x 25 - 20	4 800	6 800
			BK 130 x 30 - 15	4 800	6 800
			BK 130 x 30 - 20	4 800	6 800

Typ: BK

Korund: P- 40, 60, 80 Zirkonkorund: P- 40, 60, 80					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BK 150 x 15 - 22,2	4 500	6 000	BK 160 x 25 - 31	4 200	5 800
BK 150 x 15 - 25	4 500	6 000	BK 160 x 25 - 45	4 200	5 800
BK 150 x 25 - 20	4 500	6 000	BK 160 x 30 - 31	4 200	5 800
BK 150 x 25 - 22,2	4 500	6 000	BK 160 x 30 - 45	4 200	5 800
BK 150 x 30 - 22,2	4 500	6 000	BK 160 x 50 - 31	4 200	5 800
			BK 160 x 50 - 45	4 200	5 800

Typ: BK

Korund: P- 40, 60, 80 Zirkonkorund: P- 40, 60, 80					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BK 165 x 25 - 31	4 200	5 800	BK 200 x 30 - 45	3 400	4 800
BK 165 x 25 - 45	4 200	5 800	BK 200 x 30 - 50	3 400	4 800
BK 165 x 30 - 31	4 200	5 800	BK 200 x 50 - 31	3 400	4 800
BK 165 x 30 - 45	4 200	5 800	BK 200 x 50 - 45	3 400	4 800
BK 165 x 50 - 31	4 200	5 800	BK 200 x 50 - 50	3 400	4 800
BK 165 x 50 - 45	4 200	5 800			

Typ: BK

Korund: P- 40, 60, 80 Zirkonkorund: P- 40, 60, 80					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BK 240 x 30 - 76	2 400	3 800	BK 250 x 50 - 76	2 400	3 800
BK 240 x 50 - 76	2 400	3 800			

Typ: BKSV

Korund: P- 80, 100, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 80, 120					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
x			BKSV 130 x 25 - 15	4 800	6 800
x			BKSV 130 x 25 - 20	4 800	6 800
			BKSV 130 x 30 - 15	4 800	6 800
			BKSV 130 x 30 - 20	4 800	6 800

Typ: BKSV

Korund: P- 80, 100, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 80, 120					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BKSV 150 x 25 - 15	4 500	6 000	BKSV 160 x 25 - 31	4 200	5 800
BKSV 150 x 25 - 20	4 500	6 000	BKSV 160 x 25 - 45	4 200	5 800
BKSV 150 x 40 - 14	4 500	6 000	BKSV 160 x 30 - 31	4 200	5 800
BKSV 150 x 30 - 15	4 500	6 000	BKSV 160 x 30 - 45	4 200	5 800
BKSV 150 x 50 - 20	4 500	6 000	BKSV 160 x 50 - 31	4 200	5 800
			BKSV 160 x 50 - 45	4 200	5 800

Typ: BKSV

Korund: P- 80, 100, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 80, 120					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BKSV 165 x 25 - 31	4 200	5 800	BKSV 200 x 30 - 45	3 400	4 800
BKSV 165 x 25 - 45	4 200	5 800	BKSV 200 x 30 - 50	3 400	4 800
BKSV 165 x 30 - 31	4 200	5 800	BKSV 200 x 50 - 31	3 400	4 800
BKSV 165 x 30 - 45	4 200	5 800	BKSV 200 x 50 - 45	3 400	4 800
BKSV 165 x 50 - 31	4 200	5 800	BKSV 200 x 50 - 50	3 400	4 800
BKSV 165 x 50 - 45	4 200	5 800			

Typ: BKSV

Korund: P- 80, 100, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 80, 120					
Označení/ Code	Doporučené otáčky Recommend speed	max RPM	Označení/ Code	Doporučené otáčky Recommend speed	max RPM
BKSV 240 x 30 - 76	2 400	3 800	BKSV 250 x 50 - 76	2 400	3 800
BKSV 240 x 50 - 76	2 400	3 800			



K-ABRASIVES
czech republic

Typ: BK

Korund: P- 40, 60, 80 Zirkonkorund: P- 40, 60, 80					
Označení Code	Doporučené otáčky Recommend speed	max RPM	Označení Code	Doporučené otáčky Recommend speed	max RPM
BK 300 x 30 - 76	2 200	3 200	BK 350 x 20 - 127	1 900	2 700
BK 300 x 30 - 100	2 200	3 200	BK 350 x 20 - 132	1 900	2 700
BK 300 x 50 - 76	2 200	3 200	BK 350 x 20 - 158	1 900	2 700
BK 300 x 50 - 100	2 200	3 200	BK 350 x 30 - 127	1 900	2 700
BK 300 x 100 - 76	2 200	3 200	BK 350 x 30 - 132	1 900	2 700
BK 300 x 100 - 100	2 200	3 200	BK 350 x 30 - 158	1 900	2 700
			BK 350 x 50 - 127	1 900	2 700
			BK 350 x 50 - 132	1 900	2 700
			BK 350 x 50 - 158	1 900	2 700
			BK 350 x 75 - 127	1 900	2 700
			BK 350 x 75 - 132	1 900	2 700
			BK 350 x 75 - 158	1 900	2 700
			BK 350 x 100 - 127	1 900	2 700
			BK 350 x 100 - 132	1 900	2 700
			BK 350 x 100 - 158	1 900	2 700

Typ: BKSV

Korund: P- 80, 100, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 80, 120					
Označení Code	Doporučené otáčky Recommend speed	max RPM	Označení Code	Doporučené otáčky Recommend speed	max RPM
BKSV 300 x 30 - 76	2 200	3 200	BKSV 350 x 20 - 127	1 900	2 700
BKSV 300 x 30 - 100	2 200	3 200	BKSV 350 x 20 - 132	1 900	2 700
BKSV 300 x 50 - 76	2 200	3 200	BKSV 350 x 20 - 158	1 900	2 700
BKSV 300 x 50 - 100	2 200	3 200	BKSV 350 x 30 - 127	1 900	2 700
BKSV 300 x 100 - 76	2 200	3 200	BKSV 350 x 30 - 132	1 900	2 700
BKSV 300 x 100 - 100	2 200	3 200	BKSV 350 x 30 - 158	1 900	2 700
			BKSV 350 x 50 - 127	1 900	2 700
			BKSV 350 x 50 - 132	1 900	2 700
			BKSV 350 x 50 - 158	1 900	2 700
			BKSV 350 x 75 - 127	1 900	2 700
			BKSV 350 x 75 - 132	1 900	2 700
			BKSV 350 x 75 - 158	1 900	2 700
			BKSV 350 x 100 - 127	1 900	2 700
			BKSV 350 x 100 - 132	1 900	2 700
			BKSV 350 x 100 - 158	1 900	2 700

Typ: BK

Korund: P- 40, 60, 80 Zirkonkorund: P- 40, 60, 80		
Označení Code	Doporučené otáčky Recommend speed	max RPM
BK 400 x 30 - 158	1 700	2 300
BK 400 x 30 - 180	1 700	2 300
BK 400 x 50 - 158	1 700	2 300
BK 400 x 50 - 180	1 700	2 300
BK 400 x 100 - 158	1 700	2 300
BK 400 x 100 - 180	1 700	2 300

Typ: BKSV

Korund: P- 80, 100, 120, 150, 180, 220, 240, 280, 320, 360, 400, 600 Zirkonkorund: P- 80, 120		
Označení Code	Doporučené otáčky Recommend speed	max RPM
BKSV 400 x 30 - 158	1 700	2 300
BKSV 400 x 30 - 180	1 700	2 300
BKSV 400 x 50 - 158	1 700	2 300
BKSV 400 x 50 - 180	1 700	2 300
BKSV 400 x 100 - 158	1 700	2 300
BKSV 400 x 100 - 180	1 700	2 300